

MICROBUS INTERGRATION IN Q1686-dle

Available sizes

Character size, photo comparison.

10-301-22-AX (top)

10-301-32-AX (bottom)



Model	Speed Sign 2x165
<u>Article no</u>	<u>10-301-22-AX</u>
<u>Character height</u>	<u>165 mm</u>
<u>Reading distance</u>	<u>2-65 m</u>
<u>Number of digits</u>	<u>2 pcs</u>
<u>Character type</u>	<u>7-segment</u>
<u>Display communication</u>	<u>TCP (default IP: 192.168.1.200 port 10001)</u>
<u>Relay output</u>	<u>Yes</u>
<u>Measures</u>	<u>450 x 320 x 35 mm</u>
<u>Weight</u>	<u>5 kg</u>
<u>IP Class</u>	<u>IP65</u>
<u>Ambient temperature</u>	<u>-30°C to +40°C / -22°F to +104°F</u>
<u>Power</u>	<u>Included 24VAC PSU for either 230VAC or 110VAC</u>
<u>Consumption</u>	<u>25W</u>
<u>Pole mount clamp bracket</u>	<u>Included</u>
<u>Warranty</u>	<u>3 years</u>

Model	Speed Sign 2x230
<u>Article no</u>	<u>10-301-32-AX</u>
<u>Character height</u>	<u>230 mm</u>
<u>Reading distance</u>	<u>2-90 m</u>
<u>Number of digits</u>	<u>2 pcs</u>
<u>Connector</u>	<u>Neutrik RJ45 NE8 Connector</u>
<u>Display communication</u>	<u>TCP (default IP: 192.168.1.200 port 10001)</u>
<u>Relay output</u>	<u>Yes</u>
<u>Measures</u>	<u>450 x 320 x 35 mm</u>
<u>Weight</u>	<u>5 kg</u>
<u>IP Class</u>	<u>IP65</u>
<u>Ambient temperature</u>	<u>-30°C to +40°C / -22°F to +104°F</u>
<u>Power</u>	<u>Included 24VAC PSU for either 230VAC or 110VAC</u>
<u>Consumption</u>	<u>25W</u>
<u>Pole mount clamp bracket</u>	<u>Included</u>
<u>Warranty</u>	<u>3 years</u>